

Ratings					<h2 style="color: blue;">Gas Engine Data Sheet</h2> <p>Model : 6M33G6N0/5</p> <p>Frequency: 50HZ</p> <p>Fuel Type: Natural gas</p>															
Engine Speed (RPM)	Continuous Power (COP) (kWm/PS)		Rated Power (PRP) (kWm/PS)																	
	Gross Power	Net Power	Gross Power	Net Power																
1500	383/520	351/477	450/612	418/568																
Generator Set Output	Continuous Power (COP)		Rated Power (PRP)																	
	kW	kVA	kW	kVA																
	320	400	390	487																
Rating definitions																				
<p>Continuous Power (COP)</p> <ol style="list-style-type: none"> Power output available with constant load for unlimited time. For continuous operation at constant load. Without overload capacity. <p>Prime Power (PRP)</p> <ol style="list-style-type: none"> Power output available with varying load for unlimited time. Average power output is no more than 70% of the PRP over 24 h of operation. 100% load operation cannot exceed 500h every year. 10% overload can operate 1h within every 12h, and the accumulative overload operation cannot exceed 25h every year. 																				
<p>Note:</p> <ol style="list-style-type: none"> The power rating is in accordance with ISO 3046. Test conditions: 100 kPa, 25°C air inlet temperature, relative humidity of 30%. The derating in different altitude and temperature can be confirmed from the engineers of Baudouin. Natural gas refers to Standard Pipeline Natural gas, CNG and LNG with a methane number that is greater than 70. Consult Sales Application Engineering and perform gas analysis for fuel types that vary from these conditions. 																				
<p>Conversion table</p> <table style="width: 100%; border: none;"> <tr> <td>1 in = 25.4 mm</td> <td>1 ft = 0.3048 m</td> </tr> <tr> <td>1 cfm = 1.7 m³/h = 28.3 L/min</td> <td>1 lb_m = 0.45359 kg</td> </tr> <tr> <td>1 kW = 1.36 PS = 1.34 HP</td> <td>1 kcal/h = 1.163 W</td> </tr> <tr> <td>1 Imp gal = 4.546 lit.</td> <td>1 mm Hg = 133 Pa</td> </tr> <tr> <td>1 US gal = 3.785 lit.</td> <td>1 inch Hg = 3386 Pa</td> </tr> <tr> <td>1 BTU=1.055 kJ</td> <td>1 mm water = 9.789 Pa</td> </tr> <tr> <td>1 psi =6.89 kPa</td> <td>1 inch water = 248.64 Pa</td> </tr> <tr> <td>1 lbm.ft =1.356 J</td> <td>1 lb_f = 4.45 N</td> </tr> </table>					1 in = 25.4 mm	1 ft = 0.3048 m	1 cfm = 1.7 m ³ /h = 28.3 L/min	1 lb _m = 0.45359 kg	1 kW = 1.36 PS = 1.34 HP	1 kcal/h = 1.163 W	1 Imp gal = 4.546 lit.	1 mm Hg = 133 Pa	1 US gal = 3.785 lit.	1 inch Hg = 3386 Pa	1 BTU=1.055 kJ	1 mm water = 9.789 Pa	1 psi =6.89 kPa	1 inch water = 248.64 Pa	1 lbm.ft =1.356 J	1 lb _f = 4.45 N
1 in = 25.4 mm	1 ft = 0.3048 m																			
1 cfm = 1.7 m ³ /h = 28.3 L/min	1 lb _m = 0.45359 kg																			
1 kW = 1.36 PS = 1.34 HP	1 kcal/h = 1.163 W																			
1 Imp gal = 4.546 lit.	1 mm Hg = 133 Pa																			
1 US gal = 3.785 lit.	1 inch Hg = 3386 Pa																			
1 BTU=1.055 kJ	1 mm water = 9.789 Pa																			
1 psi =6.89 kPa	1 inch water = 248.64 Pa																			
1 lbm.ft =1.356 J	1 lb _f = 4.45 N																			
<p>Update history:</p>																				
Certified by:																				
Date	2019-10-25																			

Contents of tested gas

The technical data is based on natural gas with the following contents.

Constituent	Abbrev	%Mole
Methane	CH4	97.05
Ethane	C2H6	0.40
Ethylene	C2H4	<0.01
Propane	C3H8	0.10
Butane	C4H10	0.04
Pentane	C5H12	<0.02
Hexane	C6H14	<0.01
Nitrogen	N2	1.92
Oxygen	O2	0.49
Hydrogen	H2	<0.01
Carbon monoxide	CO	<0.01
Carbon Dioxide	CO2	<0.01
Density (at 100 kPa, 25°C)		0.6852 kg/m ³
Higher calorific value (at 100 kPa, 25°C)		36.42 MJ/m ³
Lower calorific value (at 100 kPa, 25°C)		32.81 MJ/m ³
Methane number (at 100 kPa, 25°C)		97.3

General Data

Engine model.....	6M33G6N0/5
No. of Cylinders/Valves.....	6/24
Cylinders arrangement	In line
Bore×Stroke mm (in)	150×185 (5.9×7.28)
Displacement L (in ³)	19.6 (1196)
Thermodynamic Cycle.....	4 stroke
Fuel type.....	Natural gas
Control system.....	WOODWARD
Combustion system	Spark-ignited
Fuel system	Lean Burn
Aspiration.....	Turbocharged and Intercooled
Compression ratio.....	11:1
Flywheel housing	SAE1
Flywheel.....	14"
Inertia of flywheel kg·m ² (lbm·ft ²)	4.76 (113)
Inertia of crankshaft kg·m ² (lbm·ft ²).....	2.22 (52.68)
Emission standard	N/A
Engine dimensions and weight with radiator	
- Length mm (in.).....	2797 (110)
- Width mm (in.).....	1680 (66.1)
- Height mm (in.)	1954 (76.9)
Engine dry weight kg (lbm).....	2610 (5754)
Direction of rotation.....	Anticlockwise (from flywheel side)
Max. ambient temperature restriction °C (°F).....	45 (113)

Performance

Idle speed RPM.....	700-750
Rated engine speed RPM.....	1500
Mean piston speed m/s (ft/s)	9.25 (30.3)
BMEP @ PRP Bar (psi).....	18.37 (266.6)

Air intake system

Max. temperature rise before turbocharger °C (°F).....	≤5 (41)
Air intake restriction with clean filter kPa (psi)	≤3 (0.44)
Air intake restriction with dirty filter kPa (psi)	≤5 (0.87)
Air flow Mass @ PRP kg/h (lb/hr)	1980 (4365)
Air flow Volume @ PRP m ³ /min (cfm).....	27.9 (984.7)

Fuel system

Min. gas pressure of mixer inlet kPa (psi).....	2 (0.29)
Max. gas pressure of mixer inlet kPa (psi)	7 (1.02)
Pressure loss of gas mixer kPa (psi)	0.5 (0.073)
Suction pressure max. kPa (psi).....	3 (0.435)
Max. gas inlet temperature °C (°F).....	50 (122)
Min. diameter of inlet pipe mm (in.)	40 (1.57)

Exhaust system

Max. exhaust back pressure kPa (psi)	7.5 (1.09)
Max. exhaust temperature before turbocharger °C (°F).....	730 (1346)
Max. exhaust temperature after turbocharger °C (°F).....	650 (1202)
Exhaust flow Mass @ PRP kg/h (lb/hr)	2064.6 (4551.7)
Exhaust flow Volume @ PRP m ³ /min (cfm)	94.5 (3335.3)
Min. diameter of the exhaust pipe mm (in.)	195 (7.68)
Max. bending moment at the turbocharger flange (N • m)	10
Exhaust Manifold	dry

Cooling system

Coolant capacity of engine without radiator L (Imp gal)	44 (9.68)
Coolant flow of engine pump @ rated speed m ³ /h (cfm)	18 (10.59)
Min. pressure in cooling system kPa (psi)	50 (7.26)
Max. additional restriction kPa (psi)	50 (7.26)
Min. inner diameter of coolant outlet pipe mm (in.)	45 (1.77)
Alarm temperature of coolant °C (°F).....	95 (203)
Shut down temperature of coolant °C (°F).....	98 (208.4)
Thermostat opening temp. /full open temp. °C (°F)	80/92 (176/197.6)

Fan

- rotating speed RPM	1270
- diameter mm (in.).....	1118 (44)
- number of blades	10
- Material.....	Plastic
- type.....	Belt driven pusher
- air flow m ³ /min (cfm)	720 (25411)
- power consumption kW (PS)	19 (25.8)

Intercooler system

Intercooler system type Air to Air
 Max. intake temperature after intercooler °C (°F)..... 55 (131)
 Coolant capacity of intercooler L (Imp gal)N/A
 Max. pressure drop of the intercooler kPa (psi) 12 (1.74)
 Coolant flow of intercooler @ rated speed m3/h (cfm)N/A

Lubrication system

Oil capacity Low/High L (Imp gal) 37.2/62 (8.18/13.64)
 Oil pressure at idel speed kPa (psi)..... ≥200 (29)
 Oil pressure at rated speed kPa (psi) 400~650 (58.1-94.3)
 Oil pressure limit. Lowest value kPa (psi) 200 (29)
 Oil pressure limit. Highest value kPa (psi) 1000 (145.1)
 Max. oil temperature °C (°F)..... 105 (221)
 Oil consumption %Gas ≤0.3
 Total system capacity including filter L (Imp gal) 64 (14.1)
 Oil flow L/min (cfm)..... ≥263 (9.28)

Electrical system

Electrical system voltage V24
 Starter power kW 8.5
 Battery charger current A 55
 Max. electric resistance of the starting circuit mΩ 8
 Min. sectional area of wire mm2 (in2) 70 (0.11)
 No. of teeth on flywheel ring gear 178
 No. of teeth on starter gear..... 12

Cold start capability

Min. cold start temp. without air preheating °C (°F) -13 (8.6)

Noise

Sound pressure level dB(A) 1m 99.6
 Acoustic power level dB(A) 117.1

Emission Limit

NOx mg/Nm³ ≤500
 CO g/kW·h ≤1.35
 NMHC g/kW·h ≤0.5
 HC g/kW·h..... ≤1.5

Heat balance test data

Ambient temperature	°C (°F)	28 (82.4)		
Load		100% of PRP	75% of PRP	50% of PRP
ISO standard rating	kWm (PS)	450 (612)	337 (458.3)	225 (306)
Air ratio		1.42	1.39	1.35
Engine total heat	kJ/s (BTU/s)	1111.4 (1053.5)	922.5 (874.4)	615.0 (582.9)
Heat taken away by the coolant	kJ/s (BTU/s)	127.8 (121.1)	95.8 (90.9)	63.9 (60.6)
Intercooler heat dissipating capacity	kJ/s (BTU/s)	58.46 (55.4)	43.8 (41.6)	29.2 (27.7)
Heat taken away by the exhaust up to 120°C	kJ/s (BTU/s)	290.56 (275.4)	217.9 (206.6)	145.3 (137.7)
Radiated heat to ambient	kJ/s (BTU/s)	112 (106.2)	84.0 (79.6)	56.0 (53.1)
Gas Consumption	(g/kW.h)	188	182.2	201.1
Gas Consumption	(kg/h)	84.6	61.4	45.2
Mechanical Efficiency	%	40.5	36.5	36.6
Therma Efficiency	%	42.9	38.8	38.8
Total Efficiency	%	83.4	75.3	75.4

Note: The above data are obtained from the laboratory and for reference only.