



POWERKIT ENGINE DATA SHEET

1 of 5

Ratings					Gas Engine Data Sheet																	
Engine Speed (RPM)		Continuous Power (COP) (kWm/PS)		Rated Power (PRP) (kWm/PS)																		
		Gross Power	Net Power	Gross Power	Net Power																	
1800		408/555	378/514	480/653	450/612																	
Generator Set Output		Continuous Power (COP)		Rated Power (PRP)																		
		kW	kVA	kW	kVA																	
		340	425	400	500																	
Rating definitions																						
<p>Continuous Power (COP)</p> <ol style="list-style-type: none">1. Power output available with constant load for unlimited time.2. For continuous operation at constant load.3. Without overload capacity. <p>Prime Power (PRP)</p> <ol style="list-style-type: none">1. Power output available with varying load for unlimited time.2. Average power output is no more than 70% of the PRP over 24 h of operation.3. 100% load operation cannot exceed 500h every year.4. 10% overload can operate 1h within every 12h, and the accumulative overload operation cannot exceed 25h every year.																						
Note:																						
<ol style="list-style-type: none">1. The power rating is in accordance with ISO 3046.2. Test conditions: 100 kPa, 25°C air inlet temperature, relative humidity of 30%.3. The derating in different altitude and temperature can be confirmed from the engineers of Baudouin.4. Natural gas refers to Standard Pipeline Natural gas, CNG and LNG with a methane number that is greater than 70. Consult Sales Application Engineering and perform gas analysis for fuel types that vary from these conditions.																						
Conversion table																						
<table><tbody><tr><td>1 in = 25.4 mm</td><td>1 ft = 0.3048 m</td></tr><tr><td>1 cfm = 1.7 m³/h = 28.3 L/min</td><td>1 lb_m = 0.45359 kg</td></tr><tr><td>1 kW = 1.36 PS = 1.34 HP</td><td>1 kcal/h = 1.163 W</td></tr><tr><td>1 Imp gal = 4.546 lit.</td><td>1 mm Hg = 133 Pa</td></tr><tr><td>1 US gal = 3.785 lit.</td><td>1 inch Hg = 3386 Pa</td></tr><tr><td>1 BTU=1.055 kJ</td><td>1 mm water = 9.789 Pa</td></tr><tr><td>1 psi = 6.89 kPa</td><td>1 inch water = 248.64 Pa</td></tr><tr><td>1 lbf.ft = 1.356 J</td><td>1 lb_f = 4.45 N</td></tr></tbody></table>							1 in = 25.4 mm	1 ft = 0.3048 m	1 cfm = 1.7 m ³ /h = 28.3 L/min	1 lb _m = 0.45359 kg	1 kW = 1.36 PS = 1.34 HP	1 kcal/h = 1.163 W	1 Imp gal = 4.546 lit.	1 mm Hg = 133 Pa	1 US gal = 3.785 lit.	1 inch Hg = 3386 Pa	1 BTU=1.055 kJ	1 mm water = 9.789 Pa	1 psi = 6.89 kPa	1 inch water = 248.64 Pa	1 lbf.ft = 1.356 J	1 lb _f = 4.45 N
1 in = 25.4 mm	1 ft = 0.3048 m																					
1 cfm = 1.7 m ³ /h = 28.3 L/min	1 lb _m = 0.45359 kg																					
1 kW = 1.36 PS = 1.34 HP	1 kcal/h = 1.163 W																					
1 Imp gal = 4.546 lit.	1 mm Hg = 133 Pa																					
1 US gal = 3.785 lit.	1 inch Hg = 3386 Pa																					
1 BTU=1.055 kJ	1 mm water = 9.789 Pa																					
1 psi = 6.89 kPa	1 inch water = 248.64 Pa																					
1 lbf.ft = 1.356 J	1 lb _f = 4.45 N																					
Update history:																						
Certified by:																						
Date		2019-10-25																				

Contents of tested gas

The technical data is based on natural gas with the following contents.

Constituent	Abbrev	%Mole
Methane	CH4	97.05
Ethane	C2H6	0.40
Ethylene	C2H4	<0.01
Propane	C3H8	0.10
Butane	C4H10	0.04
Pentane	C5H12	<0.02
Hexane	C6H14	<0.01
Nitrogen	N2	1.92
Oxygen	O2	0.49
Hydrogen	H2	<0.01
Carbon monoxide	CO	<0.01
Carbon Dioxide	CO2	<0.01
Density (at 100 kPa, 25°C)		0.6852 kg/m ³
Higher calorific value (at 100 kPa, 25°C)		36.42 MJ/m ³
Lower calorific value (at 100 kPa, 25°C)		32.81 MJ/m ³
Methane number (at 100 kPa, 25°C)		97.3

General Data

Engine model.....	6M33G6N0/6
No. of Cylinders/Valves.....	6/24
Cylinders arrangement	In line
Bore×Stroke mm (in)	150×185 (5.9×7.28)
Displacement L (in ³)	19.6 (1196)
Thermodynamic Cycle	4 stroke
Fuel type.....	Natural gas
Control system.....	WOODWARD
Combustion system	Spark-ignited
Fuel system	Lean Burn
Aspiration.....	Turbocharged and Intercooled
Compression ratio.....	11:1
Flywheel housing.....	SAE1
Flywheel.....	14"
Inertia of flywheel kg·m ² (lbm·ft ²)	4.76 (113)
Inertia of crankshaft kg·m ² (lbm·ft ²).....	2.22 (52.68)
Emission standard	N/A
Engine dimensions and weight with radiator	
- Length mm (in.).....	2797 (110)
- Width mm (in.).....	1680 (66.1)
- Height mm (in.)	1954 (76.9)
Engine dry weight kg (lbm).....	2610 (5754)
Direction of rotation.....	Anticlockwise (from flywheel side)
Max. ambient temperature restriction °C (°F).....	45 (113)

Performance

Idle speed RPM.....	700-750
Rated engine speed RPM.....	1800
Mean piston speed m/s (ft/s)	11.1 (36.4)
BMEP @ PRP Bar (psi).....	16.32 (236.8)

Air intake system

Max. temperature rise before turbocharger °C (°F).....	≤5 (41)
Air intake restriction with clean filter kPa (psi)	≤3 (0.44)
Air intake restriction with dirty filter kPa (psi)	≤5 (0.87)
Air flow Mass @ PRP kg/h (lb/hr)	2090 (4607)
Air flow Volume @ PRP m ³ /min (cfm).....	29.4 (1037.6)

Fuel system

Min. gas pressure of mixer inlet kPa (psi).....	2 (0.29)
Max. gas pressure of mixer inlet kPa (psi)	7 (1.02)
Pressure loss of gas mixer kPa (psi)	0.5 (0.073)
Suction pressure max. kPa (psi).....	3 (0.435)
Max. gas inlet temperature °C (°F).....	50 (122)
Min. diameter of inlet pipe mm (in.)	40 (1.57)

Exhaust system

Max. exhaust back pressure kPa (psi)	7.5 (1.09)
Max. exhaust temperature before turbocharger °C (°F).....	730 (1346)
Max. exhaust temperature after turbocharger °C (°F).....	650 (1202)
Exhaust flow Mass @ PRP kg/h (lb/hr)	2181.1 (4808)
Exhaust flow Volume @ PRP m ³ /min (cfm)	101.9 (3596.5)
Min. diameter of the exhaust pipe mm (in.)	195 (7.68)
Max. bending moment at the turbocharger flange (N · m)	10
Exhaust Manifold	dry

Cooling system

Coolant capacity of engine without radiator L (Imp gal)	44 (9.68)
Coolant flow of engine pump @ rated speed m ³ /h (cfm)	17.8 (10.47)
Min. pressure in cooling system kPa (psi)	50 (7.26)
Max. additional restriction kPa (psi)	50 (7.26)
Min. inner diameter of coolant outlet pipe mm (in.)	45 (1.77)
Alarm temperature of coolant °C (°F).....	95 (203)
Shut down temperature of coolant °C (°F).....	98 (208.4)
Thermostat opening temp. /full open temp. °C (°F)	80/92 (176/197.6)
Fan	
- rotating speed RPM	1525
- diameter mm (in.)	1118 (44)
- number of blades	10
- Material	Plastic
- type	Belt driven pusher
- air flow m ³ /min (cfm)	975 (34411)
- power consumption kW (PS)	29.2 (39.7)

Intercooler system

Intercooler system type	Air to Air
Max. intake temperature after intercooler °C (°F).....	55 (131)
Coolant capacity of intercooler L (Imp gal)	N/A
Max. pressure drop of the intercooler kPa (psi)	12 (1.74)
Coolant flow of intercooler @ rated speed m3/h (cfm)	N/A

Lubrication system

Oil capacity Low/High L (Imp gal)	37.2/62 (8.18/13.64)
Oil pressure at idel speed kPa (psi).....	≥200 (29)
Oil pressure at rated speed kPa (psi)	400~650 (58.1-94.3)
Oil pressure limit. Lowest value kPa (psi)	200 (29)
Oil pressure limit. Highest value kPa (psi)	1000 (145.1)
Max. oil temperature °C (°F).....	105 (221)
Oil consumption %Gas	≤0.3
Total system capacity including filter L (Imp gal)	64 (14.1)
Oil flow L/min (cfm).....	≥263 (9.28)

Electrical system

Electrical system voltage V	24
Starter power kW	8.5
Battery charger current A	55
Max. electric resistance of the starting circuit mΩ	8
Min. sectional area of wire mm ² (in ²)	70 (0.11)
No. of teeth on flywheel ring gear	178
No. of teeth on starter gear	12

Cold start capability

Min. cold start temp. without air preheating °C (°F)	-13 (8.6)
--	-----------

Noise

Sound pressure level dB(A) 1m	103.6
Acoustic power level dB(A)	1195

Emission Limit

NOx mg/Nm ³	≤500
CO g/kW·h	≤1.35
NMHC g/kW·h.....	≤0.5
HC g/kW·h.....	≤1.5

Heat balance test data

Ambient temperature	°C (°F)	28 (82.4)	
Load		100% of PRP	75% of PRP
ISO standard rating	kWm (PS)	480 (653)	360 (489.6)
Air ratio		1.43	1.39
Engine total heat	kJ/s (BTU/s)	1196.8 (1134.4)	993.3 (941.6)
Heat taken away by the coolant	kJ/s (BTU/s)	122.9 (116.5)	92.2 (87.4)
Intercooler heat dissipating capacity	kJ/s (BTU/s)	65.94 (62.5)	49.5 (46.9)
Heat taken away by the exhaust up to 120°C	kJ/s (BTU/s)	306.72 (290.7)	230.0 (218.0)
Radiated heat to ambient	kJ/s (BTU/s)	144.6 (137.1)	108.4 (102.8)
Gas Consumption	(g/kW.h)	189.8	197.8
Gas Consumption	(kg/h)	91.1	71.2
Mechanical Efficiency	%	40.1	36.2
Therma Efficiency	%	41.4	37.4
Total Efficiency	%	81.5	73.7

Note: The above data are obtained from the laboratory and for reference only.